

DUBL-CHEK D-100 Aerosol

Callington Haven

Chemwatch: 5147-45

Version No: 2.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 24/07/2014

Print Date: 01/08/2014

Initial Date: Not Available

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	DUBL-CHEK D-100 Aerosol
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	AEROSOLS
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Application is by spray atomisation from a hand held aerosol pack Used in NDT testing as a developer.
--------------------------	--

Details of the manufacturer/importer

Registered company name	Callington Haven		
Address	30 South Street Rydalmere 2116 NSW Australia		
Telephone	+61 2 9898 2788		
Fax	+61 2 9684 4215		
Website	www.callingtonhaven.com		
Email	sales@calhaven.com.au		

Emergency telephone number

Association / Organisation	Not Available		
Emergency telephone numbers	1800 039 008 (24 hours),+61 3 9573 3112 (24 hours)		
Other emergency telephone numbers	1800 039 008 (24 hours),+61 3 9573 3112 (24 hours)		

CHEMWATCH EMERGENCY RESPONSE

Primary Number	Alternative Number 1	Alternative Number 2
1800 039 008	+612 9186 1132	Not Available

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	3	
Toxicity	1	
Body Contact	2	
Reactivity	0	
Chronic	0	

0 = Minimum
1 = Low
2 = Moderate
3 = High
4 = Extreme

Poisons Schedule	Not Applicable
GHS Classification ^[1]	Aerosols Category 1, Eye Irrit. 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements	 
---------------------------	---

SIGNAL WORD	DANGER
--------------------	---------------

Hazard statement(s)

H222	Extremely flammable aerosol
H319	Causes serious eye irritation
AUH044	Risk of explosion if heated under confinement

Precautionary statement(s): Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s): Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.

Precautionary statement(s): Storage

P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
------------------	--

Precautionary statement(s): Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
67-63-0	NotSpec.	isopropanol
68476-85-7.	NotSpec.	hydrocarbon propellant

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes:
--------------------	---

DUBL-CHEK D-100 Aerosol

	▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor.
Ingestion	Not considered a normal route of entry. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Seek medical advice.

Indication of any immediate medical attention and special treatment needed

	For acute or short term repeated exposures to isopropanol: ▶ Rapid onset respiratory depression and hypotension indicates serious ingestions that require careful cardiac and respiratory monitoring together with immediate intravenous access. ▶ Rapid absorption precludes the usefulness of emesis or lavage 2 hours post-ingestion. Activated charcoal and cathartics are not clinically useful. Ipecac is most useful when given 30 mins. post-ingestion. ▶ There are no antidotes. ▶ Management is supportive. Treat hypotension with fluids followed by vasopressors. ▶ Watch closely, within the first few hours for respiratory depression; follow arterial blood gases and tidal volumes. ▶ Ice water lavage and serial haemoglobin levels are indicated for those patients with evidence of gastrointestinal bleeding.
--	--

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

	▶ Water spray or fog. ▶ Foam. ▶ Dry chemical powder. ▶ BCF (where regulations permit).
--	---

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with strong oxidising agents as ignition may result
-----------------------------	---

Advice for firefighters

Fire Fighting	▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	▶ Liquid and vapour are highly flammable. ▶ Severe fire hazard when exposed to heat or flame. ▶ Vapour forms an explosive mixture with air. ▶ Severe explosion hazard, in the form of vapour, when exposed to flame or spark.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

DUBL-CHEK D-100 Aerosol

Minor Spills	▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Wear protective clothing, impervious gloves and safety glasses. ▶ Shut off all possible sources of ignition and increase ventilation.
Major Spills	▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear breathing apparatus plus protective gloves.
	Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps.
Other information	▶ Store in original containers in approved flame-proof area. ▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped. ▶ No smoking, naked lights, heat or ignition sources. ▶ Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Aerosol dispenser. ▶ Check that containers are clearly labelled.
Storage incompatibility	Avoid storage with oxidisers

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	isopropanol	Isopropyl alcohol	983 mg/m ³ / 400 ppm	1230 mg/m ³ / 500 ppm	Not Available	Not Available
Australia Exposure Standards	hydrocarbon propellant	LPG (liquified petroleum gas)	1800 mg/m ³ / 1000 ppm	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	TEEL-0	TEEL-1	TEEL-2	TEEL-3
isopropanol	400 ppm	400 ppm	2000 ppm	2000 ppm
hydrocarbon propellant	1000 ppm	2000 ppm	2000 ppm	2000 ppm

Ingredient	Original IDLH	Revised IDLH
isopropanol	12,000 ppm	2,000 [LEL] ppm
hydrocarbon propellant	19,000 [LEL] ppm	2,000 [LEL] ppm

Exposure controls

Appropriate engineering controls	- Use in a well-ventilated area - General exhaust is adequate under normal operating conditions.
----------------------------------	---

DUBL-CHEK D-100 Aerosol

Personal protection	    
Eye and face protection	No special equipment for minor exposure i.e. when handling small quantities. OTHERWISE: For potentially moderate or heavy exposures: ▶ Safety glasses with side shields. ▶ NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.
Skin protection	See Hand protection below
Hands/feet protection	▶ No special equipment needed when handling small quantities. ▶ OTHERWISE: ▶ For potentially moderate exposures: ▶ Wear general protective gloves, eg. light weight rubber gloves. ▶ For potentially heavy exposures: ▶ Wear chemical protective gloves, eg. PVC. and safety footwear.
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. OTHERWISE: ▶ Overalls. ▶ Skin cleansing cream. ▶ Eyewash unit.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

DUBL-CHEK D-100 Aerosol Not Available

Material	CPI
----------	-----

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant.

Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	AX-AUS / Class1	-
up to 50	1000	-	AX-AUS / Class 1
up to 50	5000	Airline *	-
up to 100	5000	-	AX-2
up to 100	10000	-	AX-3
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	22aer Clear highly flammable liquid with white sediment on bottom; dispersible in water. Sweet solvent odour. Dries to white powder.		
Physical state	Liquid	Relative density (Water = 1)	Not Available

DUBL-CHEK D-100 Aerosol

Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not available.
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not available.	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	11.7 (isoprop)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	9.5	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1.8	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	345 @ 21C	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution(1%)	Not Applicable
Vapour density (Air = 1)	>1	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	▶ Elevated temperatures. ▶ Presence of open flame. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.
Ingestion	Not normally a hazard due to physical form of product. The liquid is discomforting Ingestion may result in nausea, abdominal irritation, pain and vomiting
Skin Contact	The liquid may produce skin discomfort following prolonged contact. Defatting and/or drying of the skin may lead to dermatitis The material may accentuate any pre-existing skin condition
Eye	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
Chronic	Long term or repeated ingestion exposure of isopropanol may produce incoordination, lethargy and reduced weight gain. Repeated inhalation exposure to isopropanol may produce narcosis, incoordination and liver degeneration. Animal data show developmental effects only at exposure levels that produce toxic effects in the adult animals. Isopropanol does not cause genetic damage in bacterial or mammalian cell cultures or in animals.

DUBL-CHEK D-100 Aerosol	TOXICITY	IRRITATION
	Not Available	Not Available

DUBL-CHEK D-100 Aerosol

isopropanol	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 12800 mg/kg	Eye (rabbit): 10 mg - moderate
	Inhalation (Mouse) LC50: 53000 mg/m3/4h	Eye (rabbit): 100 mg - SEVERE
	Inhalation (Rat) LC50: 72600 mg/m3/4h	Eye (rabbit): 100mg/24hr-moderate
	Intraperitoneal (Guinea pig) LD50: 2560 mg/kg	Skin (rabbit): 500 mg - mild
	Intraperitoneal (Mouse) LD50: 4477 mg/kg	
	Intraperitoneal (Rabbit) LD50: 667 mg/kg	
	Intraperitoneal (Rat) LD50: 2735 mg/kg	
	Intravenous (Mouse) LD50: 1509 mg/kg	
	Intravenous (Rabbit) LD50: 1184 mg/kg	
	Intravenous (Rat) LD50: 1088 mg/kg	
	Oral (Mouse) LD50: 3600 mg/kg	
	Oral (Rabbit) LD50: 6410 mg/kg	
	Oral (Rat) LD50: 5000 mg/kg	
	Oral (rat) LD50: 5045 mg/kg	
	Not Available	Not Available
hydrocarbon propellant	TOXICITY	IRRITATION
	Not Available	Not Available

Not available. Refer to individual constituents.

ISOPROPANOL	Isopropanol is irritating to the eyes, nose and throat but generally not to the skin. Prolonged high dose exposure may also produce depression of the central nervous system and drowsiness. Few have reported skin irritation. It can be absorbed from the skin or when inhaled.
HYDROCARBON PROPELLANT	No significant acute toxicological data identified in literature search. inhalation of the gas

Acute Toxicity	⊖	Carcinogenicity	⊖
Skin Irritation/Corrosion	⊖	Reproductivity	⊖
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	⊖
Respiratory or Skin sensitisation	⊖	STOT - Repeated Exposure	⊖
Mutagenicity	⊖	Aspiration Hazard	⊖

Legend: ✓ – Data required to make classification available
 ✗ – Data available but does not fill the criteria for classification
 ⊖ – Data Not Available to make classification

CMR STATUS

CARCINOGEN	hydrocarbon propellant	Australia Exposure Standards - Carcinogens	Carc. 1B
------------	------------------------	--	----------

SECTION 12 ECOLOGICAL INFORMATION

DUBL-CHEK D-100 Aerosol

Toxicity

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Not Available	Not Available	Not Available

Bioaccumulative potential

Ingredient	Bioaccumulation
Not Available	Not Available

Mobility in soil

Ingredient	Mobility
Not Available	Not Available

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	- Consult State Land Waste Management Authority for disposal. - Discharge contents of damaged aerosol cans at an approved site. - Allow small quantities to evaporate. DO NOT incinerate or puncture aerosol cans.
------------------------------	---

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	NO
HAZCHEM	2YE

Land transport (ADG)

UN number	1950				
Packing group	Not Applicable				
UN proper shipping name	AEROSOLS				
Environmental hazard	No relevant data				
Transport hazard class(es)	<table><tr><td>Class</td><td>2.1</td></tr><tr><td>Subrisk</td><td>Not Applicable</td></tr></table>	Class	2.1	Subrisk	Not Applicable
Class	2.1				
Subrisk	Not Applicable				
Special precautions for user	<table><tr><td>Special provisions</td><td>63 190 277 327</td></tr><tr><td>Limited quantity</td><td>See SP 277</td></tr></table>	Special provisions	63 190 277 327	Limited quantity	See SP 277
Special provisions	63 190 277 327				
Limited quantity	See SP 277				

Air transport (ICAO-IATA / DGR)

UN number	1950						
Packing group	Not Applicable						
UN proper shipping name	Aerosols, flammable						
Environmental hazard	No relevant data						
Transport hazard class(es)	<table><tr><td>ICAO/IATA Class</td><td>2.1</td></tr><tr><td>ICAO / IATA Subrisk</td><td>Not Applicable</td></tr><tr><td>ERG Code</td><td>10L</td></tr></table>	ICAO/IATA Class	2.1	ICAO / IATA Subrisk	Not Applicable	ERG Code	10L
ICAO/IATA Class	2.1						
ICAO / IATA Subrisk	Not Applicable						
ERG Code	10L						

DUBL-CHEK D-100 Aerosol

Special precautions for user	Special provisions	A145A167A802
	Cargo Only Packing Instructions	203
	Cargo Only Maximum Qty / Pack	150 kg
	Passenger and Cargo Packing Instructions	203
	Passenger and Cargo Maximum Qty / Pack	75 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Y203
	Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee)

UN number	1950
Packing group	Not Applicable
UN proper shipping name	AEROSOLS
Environmental hazard	No relevant data
Transport hazard class(es)	IMDG Class 2.1
	IMDG Subrisk See SP63
Special precautions for user	EMS Number F-D , S-U
	Special provisions 63 190 277 327 344 959
	Limited Quantities See SP277

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

isopropanol(67-63-0) is found on the following regulatory lists	"IOFI Global Reference List of Chemically Defined Substances", "International Maritime Dangerous Goods Requirements (IMDG Code)", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "Australia Exposure Standards", "FisherTransport Information", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "Australia Inventory of Chemical Substances (AICS)", "Joint FAO/WHO Expert Committee on Food Additives (JECFA) - Specifications for Flavourings", "OSPAR National List of Candidates for Substitution – Norway", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "Australia National Pollutant Inventory", "OECD Existing Chemicals Database", "Sigma-AldrichTransport Information", "Australia High Volume Industrial Chemical List (HVICL)", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Hazardous Substances Information System - Consolidated Lists", "International Fragrance Association (IFRA) Survey: Transparency List", "IMO IBC Code Chapter 17: Summary of minimum requirements", "Acros Transport Information"
hydrocarbon propellant(68476-85-7.) is found on the following regulatory lists	"International Council of Chemical Associations (ICCA) - High Production Volume List", "International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 1", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "Australia Exposure Standards", "Australia - Tasmania - Work Health and Safety Regulations 2012 - Hazardous Chemicals at Major Hazard Facilities (and their Threshold Quantity) - Table 15.1", "Australia - New South Wales - Work Health and Safety Regulation 2011 - Hazardous chemicals at major hazard facilities (and their threshold quantity) - Table 15.1", "Australia - South Australia - Work Health and Safety Regulations 2012 - Schedule 15—Hazardous chemicals at major hazard facilities (and their threshold quantity) Table 15.1", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Australia - New South Wales -Work Health and Safety Regulation 2011 - Hazardous chemicals", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "OECD List of High Production Volume (HPV) Chemicals", "Australia Inventory of Chemical Substances (AICS)", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "International Numbering System for Food Additives", "International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft", "International Chemical Secretariat (ChemSec) SIN List ("Substitute It Now!)", "International Society of Automotive Engineers (SAE) Declarable Substances Chemical List - ARP9536", "Australia Dangerous Goods Code (ADG Code) - Packing Instruction - Liquefied and Dissolved

Gases", "Australia High Volume Industrial Chemical List (HVICL)", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "Australia Work Health and Safety Regulations 2011 - Hazardous chemicals at major hazard facilities and their threshold quantity", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia - Queensland Work Health and Safety Regulation - Hazardous chemicals at major hazard facilities (and their threshold quantity)"

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.