

# MATERIAL SAFETY DATA SHEET

# 1. PRODUCT IDENTIFICATION

Product Name :	Methane and Argon Balance
Chemical Family :	Hydrocarbon and Inert Gases Mixture
Manufacturer :	Leeden National Oxygen Ltd 21 Tanjong Kling Road Singapore 628047

Emergency Phone Number : +65 6265 0406

# 2. COMPOSITION and INFORMATION ON INGREDIENTS

CHEMICAL	CHEMICAL	CAS #	MOLE	EXPOSURE LIMITS IN AIR				
NAME	FORMULA		%	ACGIH-TLV		OSHA	OSHA-PEL	
				TWA ppm	STEL ppm	TWA ppm	STEL ppm	
Argon	Ar	7440-37-1	90	Non established	Non established	Non established	Non established	
Methane	CH4	74-82-8	10	1000	Non estableshed	Non estableshed	Non estableshed	

## **3. HAZARD IDENTIFICATION**

#### **Physical Hazards :**

Compressed / Flammable Gas **Inhalation Hazard :** Mixture acts as a simple asphyxiant by displacing air necessary for life. Symptoms include rapid respiration, muscular incoordination, fatigue, dizziness, nausea, vomiting, unconsciousness, and death.

#### 4. FIRST – AID MEASURES

#### Inhalation :

If adverse effects occur, remove to uncontaminated area. Get medical attention. **Skin Contact :** Wash exposed skin with soap and water. **Eye Contact :** Flush eyes with plenty of water. **Ingestion :** If a large amount is swallowed, get medical attention.

# 5. FIRE-FIGHTING MEASURES

#### Fire and explosion Hazards :

Flammable Gas. Container may rupture or explode if exposed to heat. Flammable Limits: vol % in air at 1 atm Methane

Lower : 5 Upper : 15

**Fire Extinguishing Materials :** Carbon dioxide, regular dry chemical.



# MATERIAL SAFETY DATA SHEET

#### Fire Fighting

Cool containers with water spray until well after fire is out. Stay away from ends of tanks. Stop flow of gas.

# 6. ACCIDENTAL RELEASE MEASURES

#### **Occupational release :**

Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Use proper protective equipment in the event of a significant release from cylinder. Stop leak if possible without personal risk. **Water Release :** Collect spilled material using mechanical equipment. Keep out of water supplies and sewers. **Soil Release :** 

Absorb spilled material using suitable absorbents. Contact skilled party to remove contaminated materials.

## 7. HANDLING and STORAGE

#### HANDLING:

Operators should wear protective clothing while handling this gas. If ventilation controls are not adequate to provide sufficient oxygen content, proper respiratory protection equipment should be provided. **STORAGE:** Cylinders should be stored upright and be secured firmly to prevent falling.

Protect cylinders against extreme weather and from dampness from ground to prevent rusting. Stored cylinders in well ventilated area, away from direct heat and ignition source.

Do not allow area where cylinders are stored to exceed  $52^{\circ}$ C.

## 8. EXPOSURE CONTROLS - PERSONAL PROTECTION

Exposure Limits : No occupational exposure limits established.
Ventilation : Provide local exhaust ventilation system. Ensure compliance with applicable exposure limit .
Eye Protection : Eye protection recommended.
Respirator : Under conditions of frequent use or exposure, respiratory protection may be needed.

## 9. PHYSICAL and CHEMICAL PROPERTIES

#### GENERAL INFORMATION:

Physical State :	Gas
Molecular weight :	37.56
Vapor Pressure :	150 Bar
Appearance, odor and color :	Color : Colorless
	Odor : Odorless

## **10. STABILITY and REACTIVITY**

STABILITY: Stable at standard temperatures within shelf-life. REACTIVITY: Consider as non-reactive. Avoid incompatible materials. CONDITIONS TO AVOID : Cylinders exposed to high temperatures or direct flame can rupture or burst.

## 11. TOXICOLOGICAL INFORMATION

No toxicity data is available





# MATERIAL SAFETY DATA SHEET

12. ECOLOGICAL INFORMATION	12.	ECOL	OGICAL	<b>INFORMATION</b>
----------------------------	-----	------	--------	--------------------

Fish Toxicity : Not available

Invertebrate Toxicity : Not Available.

# 13. DISPOSAL CONSIDERATIONS

# PREPARING WASTES FOR DISPOSAL:

Waste disposal must be in accordance with appropriate local regulations. Never attempt to dispose off residual locally, return cylinders with residual to gas suppliers.

## 14. TRANSPORTATION INFORMATION

PROPER SHIPPING NAME:	Compressed Gases, Flammable, N. O. S.
HAZARD CLASS:	2.1
UN NUMBER:	UN 1954

## **15. REGULATORY INFORMATION**

End users are required to have license to purchase, store and use according to local NEA regulations. Disposal of the materials are required to adhere to environmental public health (toxic Industrial Waste) Regulations. Regulated chemicals can be found on the NEA website .

# **16. OTHER INFORMATION**

When two or more gases or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce and use the mixture. Consult an Industrial Hygienist or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

# The Information, recommendations and data contained in this document are intended to be used by properly trained and qualified personnel.

Leeden National Oxygen Ltd makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty of merchantability or fitness for use. Leeden National Oxygen Ltd shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise from any publications, use or reliance upon the information herein. End of Document