enthone

Safety Data Sheet

Safety Data Sheet

Section 1. Identification

Product name	: MICROFAB® NI 200 B
Product code	: 410340
Uses advised against	: Consumer, private households, general public
Product type	: Liquid.
Date of issue/Date of revision	: April 24 2015.

Manufacturer - Supplier	Telephone no.:	Fax no.	Emergency phone:
Enthone Inc 350 Frontage Road West Haven, CT 06516	Tel: (203) 934-8611	Fax:(203) 799-8179	UNITED STATES AND CANADA: Tel: 800-424-9300 INTERNATIONAL, CALL Tel: +1 703-527-3887 (collect calls accepted) Enthone Chemtrec #7827
Alent Enthone Chemistry Trading (Shanghai) Co., Ltd. Rm 201, No.388 of Muhua North Road, Fengxian District, Shanghai	Tel: 86-21-6390 0600	Fax: 86-21-50912810	Tel: 0532-8388 9090 (24-hour)
Enthone Chemistry A Division of Alent Singapore Pte Ltd 26 Tuas West Road Singapore 638382	Tel: (65) 6861 1773	Fax: (65) 6862 3327	Tel: (65) 6861 1773
ENTHONE SDN. BHD. 111, Lorong IKS Juru 5, Taman Perindustrian Ringan Juru, 14100 Simpang Ampat, Penang, Malaysia	Tel: 60 - 4 502 6164	Fax: (604) 506 0621	Tel: 60 - 4 502 6164
Enthone Korea 1Ra 310, Sihwa Industrial Complex, 1247-9, Jungwang-Dong, Siheung-Si, Gyeonggi-Do, Korea	Tel: 82-31-432-4100	Fax: 82-31-432-4900	Tel: 82-31-432-4100
Enthone Inc. Taiwan Branch 2F, B Building, No. 10, Luxing Street, Luzhu District, 33849 Taoyuan City, Taiwan, R.O.C.	Tel: 03-312-0280	Fax: 03-312-0380	Tel: 886-937408981
Alent Japan Company - Enthone 480-28 Higashitoyoda, Hiratsuka, Kanagawa 254-0082, Japan	Tel: 81-463-51-4330	Fax: 81-463-55-2588	Tel: 81-463-51-4330
Enthone India A Division of Cookson India Pte. Ltd Developed Plot no 16, North Phase, SIDCO Industrial estate, Ambattur, Chennai - 600098.	Tel: 91-44-26252666	Fax: 91-44-26258627	Tel: 91-44-26252666

Enthone Page: 2/13 April 24 2015.

Section 2. Hazards identification

Classification of the substance or mixture	: RESPIRATORY SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 2 CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION (Unborn child) - Category 1B SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. May damage the unborn child. Suspected of causing genetic defects. Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life with long lasting effects.
Precautionary statements	, , , , , , , , , , , , , , , , , , ,
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. In case of inadequate ventilation wear respiratory protection. Avoid release to the environment. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
Response	: Collect spillage. Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not	: None known.

Other hazards which do not : None known. result in classification

Section 3. Composition/information on ingredients

Substance/mixture : Mixture		
Ingredient name	%	CAS number
Nickel Compound	20-30	-
Inorganic acid Nickel Salt	1-10 0.1-1.0	-

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 3. Composition/information on ingredients

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 30 minutes, keeping eyelids open. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or symptoms, avoid further exposure.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptom	<u>s/effects, acute and delayed</u>
Potential acute health e	ffects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/sy</u>	<u>mptoms</u>
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: wheezing and breathing difficulties asthma reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Continued on next page

Section 4. First aid measures

Indication of immediate med	dica	l attention and special treatment needed, if necessary
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

•	
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: nitrogen oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.	

Section 6. Accidental release measures

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	
Protective measures :	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general : occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, : including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

<u>Control parameters</u> <u>Occupational exposure limits</u>

Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
Nickel Compound	ACGIH TLV (United States, 4/2014). Notes as Ni TWA: 0.1 mg/m ³ , (as Ni) 8 hours. Form: Inhalable fraction ACGIH TLV (United States, 2005). Notes: As Nickel
Inorganic acid	TWA: 0.1 mg/m ³ 8 hours. Form: Soluble ACGIH TLV (United States, 4/2014). Notes Refers to Appendix A Carcinogens. Inhalable fraction. See Appendix C, paragraph A. Inhalable Particulate Mass TLVs (IPM-TLVs) for those materials that are hazardous when deposited anywhere in the respiratory tract. ACGIH 2005 Adoption STEL: 6 mg/m ³ 15 minutes. Form: Inhalable fraction
Nickel Salt	TWA: 2 mg/m ³ 8 hours. Form: Inhalable fraction ACGIH TLV (United States, 4/2014). TWA: 0.1 mg/m ³ , (as Ni) 8 hours. Form: Inhalable fraction ACGIH TLV (United States, 2003). Notes: As Nickel TWA: 1.5 mg/m ³ 8 hours. Form: Metallic form ACGIH TLV (United States, 8/2005). Notes As Nickel TWA: 0.1 mg/m ³ 8 hours. Form: Soluble Nickel
ppropriate engineering ontrols	 Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineerin controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
nvironmental exposure ontrols	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
ndividual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, befor

	eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.
	Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
protection	: Safety eyewear complying with an approved standard should be used when a risk

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	d.	
Color	en.	
Odor	acteristic.	
Odor threshold	available.	
рН		
Melting point	available.	
Boiling point)°C (>212°F)	
Flash point	available.	
Evaporation rate	available.	
Flammability (solid, gas)	flammable in the pres	ence of the following materials or conditions: open flames, e and heat.
Lower and upper explosive (flammable) limits	available.	
Vapor pressure	available.	
Vapor density	available.	
Relative density	5	
Solubility	ly soluble in the followi	ng materials: cold water and hot water.
VOC	g/l	
Partition coefficient: n- octanol/water	available.	
Auto-ignition temperature	available.	
Decomposition temperature	available.	
Viscosity	available.	

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Incompatibility with various substances	:	Highly reactive or incompatible with the following materials: alkalis. Reactive or incompatible with the following materials: oxidizing materials, reducing materials, combustible materials, metals and acids. Slightly reactive or incompatible with the following materials: organic materials and moisture.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization	:	Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Routes of entry : Dermal contact. Inhalation. Ingestion.				
Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
Nickel Compound	LDLo Oral	Mouse	250 mg/kg	-
Inorganic acid	LD50 Oral	Mouse	3450 mg/kg	-
-	LD50 Oral	Rat	2500 mg/kg	-
	LD50 Oral	Rat	2660 mg/kg	-
	LDLo Dermal	Child	1500 mg/kg	-
	LDLo Dermal	Infant	1200 mg/kg	-
	LDLo Dermal	Man	2430 mg/kg	-
	LDLo Oral	Human	214.28 mg/kg	-
	LDLo Oral	Rat	3000 mg/kg	-
	LDLo Oral	Woman	200 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Inorganic acid	Skin - Mild irritant	Human		72 hours 15 milligrams Intermittent	-

Sensitization

Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Inorganic acid		Experiment: In vitro Subject: Mammalian-Human	Positive

Carcinogenicity

No applicable toxicity data

Reproductive toxicity

Section 11. Toxicological information

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Inorganic acid	Positive	Positive	Positive	Rat - Female	Oral: 1003 mg/ kg	-
	-	-	Positive	Rat - Female	Oral: 1600 mg/ kg	-
	-	Positive	-	Rat - Male	Oral: 45 g/kg	-

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	Route of exposure	Target organs
Nickel Compound Nickel Salt		Not determined Not determined

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure Potential acute health effects

r otential acute ficaltif cheets		
Eye contact	No known significant effects or critical hazards.	
Inhalation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Skin contact	May cause an allergic skin reaction.	
Ingestion	No known significant effects or critical hazards.	

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: wheezing and breathing difficulties asthma reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Section 11. Toxicological information

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
General	: Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: Suspected of causing genetic defects.
Teratogenicity	: May damage the unborn child.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates	
Route	ATE value
Oral	77662.6 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Inorganic acid	Acute LC50 45.5 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 133000 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 75 mg/l Marine water Chronic NOEC 6000 µg/l Fresh water	Fish - Pagrus major Daphnia - Daphnia magna	96 hours 21 days
	Chronic NOEC 2100 µg/l Fresh water	Fish - Oncorhynchus mykiss	87 days

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Nickel Compound	-	5613	high
Inorganic acid	-1.09	-	low

Mobility in soil

Continued on next page

MICROFAB® NI 2	200 B	
410340		

Section 12. Ecological information

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product	: No known specific national and/or regional regulations applicable to this product (including its ingredients).
International lists	
National inventory	
Australia	: All components are listed or exempted.

Section 15. Regulatory information

Canada	: At least one component is not listed in DSL but all such components are listed in NDSL.
China	: At least one component is not listed.
Europe	: All components are listed or exempted.
Japan	: All components are listed or exempted.
New Zealand	: All components are listed or exempted.
Philippines	: All components are listed or exempted.
Republic of Korea	: All components are listed or exempted.
United States	: All components are listed or exempted.

Section 16. Other information

<u>History</u>	
Date of issue/Date of revision	: April 24 2015.
Date of previous issue	: No previous validation.
Version	: 1
Prepared by	 Regulatory Affairs Department Enthone Inc 350 Frontage Road West Haven, CT 06516 Phone: (203) 934-8611 Fax: (203) 799-8179 enthonemsds@enthone.com www.enthone.com
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Procedure used to derive the classification

Classification	Justification
Resp. Sens. 1, H334	Calculation method
Skin Sens. 1, H317	Calculation method
Muta. 2, H341	Calculation method
Carc. 1A, H350	Calculation method
Repr. 1B, H360 (Unborn child)	Calculation method
STOT RE 1, H372	Calculation method
Aquatic Acute 1, H400	Calculation method
Aquatic Chronic 1, H410	Calculation method

References

: Not available.

 \blacksquare Indicates information that has changed from previously issued version.

Notice to reader

Section 16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

4.5b3271

